

RURY PRECYZYJNE

Rury stalowe, precyzyjne bez szwu, oliwione z atestem 3.1B, w gatunku St 52.4 lub St 37.4, NBK-HPL, wykonane zgodnie z DIN 2391, znakowane..



Wymiar śred.zew.x grub. ścianki	max.ciśnienie pracy [bar]	
	St 37.4 GL	St 52.4 GL
6x1,00 mm	446	641
8x1,00 mm	334	481
8x1,50 mm	501	721
10x1,50 mm	425	611
10x2,00 mm	566	815
12 x1,50 mm	354	509
12x2,00 mm	472	679
14x1,50 mm	303	436
14x2,00 mm	404	582
14x2,50 mm	506	728
15x1,50 mm	283	407
15x2,00 mm	377	543
15x2,50 mm	472	679
15x3,00 mm	566	815
16x1,50 mm	265	382
16x2,00 mm	354	509
16x2,50 mm	442	637
16x3,00 mm	531	764
18x1,50 mm	236	339
18x2,00 mm	314	452
18x2,50 mm	393	566
18x3,00 mm	472	679
20x2,00 mm	283	407
20x2,50 mm	354	509
20x3,00 mm	425	611
22x2,00 mm	257	370
22x2,50 mm	322	463
22x3,00 mm	386	555
22x3,50 mm	450	648
25x3,00 mm	340	489
25x3,50 mm	396	570
25x4,00 mm	453	652
28x2,50 mm	253	364
28x3,00 mm	303	436
28x3,50 mm	354	509
30x3,00 mm	283	407
30x3,50 mm	330	475
30x4,00 mm	377	543
35x3,00 mm	242	349
35x3,50 mm	283	407
35x4,00 mm	323	465
38x4,00 mm	298	429
38x4,50 mm	335	482
38x5,00 mm	372	536
42x3,00 mm	202	291
42x4,00 mm	269	388
50x6,00 mm	340	489
65x5,00 mm	260	380
65x8,00 mm	348	501
75x6,00 mm	200	320